


VOMAT[®]
ENERGY-EFFICIENT FILTER & COOLING SYSTEMS



VOMAT[®]

www.vomat.de

Vomat ZFA 1200 (Base Module)

Central Systems

VOMAT GmbH


Am Wasserturm 2, 08233 Treuen
Telephone: +49-37468-6780-0
Fax: +49-37468-6780-10
Email: info@vomat.de

ENERGY EFFICIENT

MODULAR

COMPACT

Central Control



VOMAT ZFA central systems consist of separate modules. Their advantage is their compatibility. The modules are assembled according to the customer's system requirements.

Central Control

- + For module linkage
- + For controlling external components such as machine supply pumps

Central Systems - Vomat ZFA 3600



Standard Model ZFA 1200

Filter Unit

- + Single unit dimensions:
1200 x 1200 x 2200 mm (L x W x H)
- + Medium is filtered in full flow
- + Filtration grade: 3 - 5 µm
- + Demand-oriented, energy-efficient filtration via frequency controlled system pump
- + PLC control
- + Supply voltage: 3 ~ 400 V

FILTRATION SYSTEMS OF TOMORROW

We produce everything according to the customer requirements ranging from the standard system to a customized complete solution

ALL FROM ONE SOURCE

VOMAT®

Installation and commissioning of the complete system including piping on customer request

Cooling Unit

- + Cooling performance according to customer requirements
- + Control accuracy: +/- 0,2 K
- + Optionally also cold-water operated
- + Heat removal via external condenser
- + PLC control

Machine Supply Pumps



Disposal Unit

- + Sedimentator with fully automatic collection of recyclable material with a residual moisture between 5% -10%
- + User friendly disposal directly into a transport container from the recycling companies
- + PLC Control
- + Single unit dimensions:
1600 x 1200 x 2200 mm (L x W x H)
- + Optional fill level limitation in the disposal container

Disposal Unit ZFA

